



"Your Source For Packaging, Shipping & Safety Supplies"
"Ship right with Wrap-Tite"



Performance Hand Film Technical Data Sheet



- Easy release & good cling
- Stiff & Strong
- Replaces thicker film for a lower per unit cost
- Available in various colors (Dark & Tinted) in certain gauges – Black, Blue, Green, Red, Orange, Yellow, Purple, White

(Custom Colors are available up on request)

- Product Categories – PHF, ZPHF

Thickness	ASTM D-4649	Gauge	40 ga	43 ga	45 ga	47 ga	51 ga	55 ga	57 ga	63 ga
Tensile Ultimate MD	ASTM D-882	PSI	5900	5900	5950	5950	6100	6100	6250	6250
Tensile Ultimate TD	ASTM D-882	PSI	3900	3900	3950	3950	4100	4100	4100	4100
Tensile Yield MD	ASTM D-882	PSI	1200	1200	1250	1250	1275	1275	1300	1300
Tensile Yield TD	ASTM D-882	PSI	1150	1150	1200	1200	1225	1225	1250	1250
Elongation MD	ASTM D-882	%	350	350	365	365	375	375	380	380
Elongation TD	ASTM D-882	%	550	550	570	570	590	590	600	600
Elmendorf Tear MD	ASTM D-1922	g/mil	350	350	350	350	350	350	350	350
Elmendorf Tear TD	ASTM D-1922	g/mil	600	600	600	600	600	600	600	600
Cling@100%	ASTM D-5458	g/in	180	180	180	180	180	180	180	180

- *All values are representative of typical film performance and are not to be construed as manufacturing and/or sales specifications.*

Email: info@wraptite.com, **B2B:** www.wraptite.com

Head Quarters: 6200 Cochran Road, Solon, Ohio 44139

Phone: 440-349-5400

Mfg Website: www.wraptite.com/manufacturing/

Manufacturing: 6075 Cochran Road, Solon, Ohio 44139

Fax: 440-349-5432